

# DOWSIL™ Sealants for the professional building trades

Quality products deserve a quality name



## Applications

- Glazing
- Tub, tile & ceramic
- HVAC/R
- High-temperature applications
- General purpose

## DOWSIL™ Construction Sealants

Performance you can depend on at a price you can afford.

- 100% silicone rubber
- Resist sunlight and weather extremes; form long-lasting, water-resistant seals
- Remain flexible; won't become brittle, shrink or crack over time
- One-part, ready-to-use products for fast, no-mix application
- Available in 10.3 fl oz cartridges – many with removable, reusable, or resealable nozzles

## DOWSIL™ 999A Silicone Glazing Sealant

- For general glazing, backlite replacement, skylight installations; may be used to repair weather stripping and gaskets
- Can be used on most glass, plastics, metal, repainted surfaces, fiberglass, ceramics and aluminum
- Available in clear, white, translucent white, bronze, black and aluminum

## DOWSIL™ Silicone Glazing Sealant

- Can be used on most glass, plastics, metal, repainted surfaces, fiberglass and aluminum
- Available in clear, white, translucent white, bronze, black and aluminum

## DOWSIL™ General Purpose Silicone Sealant

- For use as a bedding material; to create formed-in-place gaskets and bumpers; to adhere trim, nameplates and signs; to seal around sinks, faucets, showers, tubs, toilets and vents and in most above-water marine applications
- Clear and white colors meet the requirements of FDA 21 CFR 177.2600
- Available in clear, white, black and aluminum

## DOWSIL™ 786 Sealant M

- Can be used as an adhesive, sealant or grout for repairing or replacing ceramic tiles and in many other plumbing applications; also used for sealing tub and shower enclosures
- Standard colors meet the requirements of FDA 21 CFR 177.2600
- Available in clear, white, snowy white, translucent white and almond

## DOWSIL™ HVAC/R Sealant

- For heating, ventilation, air conditioning and refrigeration applications; can be used on most glass, plastic, metal, painted surfaces, fiberglass and ceramic
- Meets the requirements of FDA 21 CFR 177.2600
- Available in clear, white and aluminum



### DOWSIL™ Hi-Temp Sealant Red

- Can be used on bag filters in smokestacks or for sealing fired heaters, access doors and flanged pipe joint flues on gas appliances; heating elements in appliances; and oven doors
- Performs from -40 to 500°F (-40 to 260°C) for continuous operation and up to 550°F (288°C) for intermittent exposure
- Available in red

### For more information

Learn more about Dow's full range of High Performance Building solutions by visiting us online at [dow.com/construction](http://dow.com/construction).

Dow has sales offices, manufacturing sites and science and technology laboratories around the globe. Find local contact information at [dow.com/contactus](http://dow.com/contactus).



Dow High Performance Building website:  
[dow.com/construction](http://dow.com/construction)



Contact Dow High Performance Building:  
[dow.com/customersupport](http://dow.com/customersupport)

 Visit us on Twitter  
[@DowHPBuilding](https://twitter.com/DowHPBuilding)

 Visit us on LinkedIn  
[Dow High Performance Building](https://www.linkedin.com/company/dow-high-performance-building)

Images: dow\_40390732479, dow\_40717061157, dow\_40388843960

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED IN THIS DOCUMENT. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE ON THE DOW WEBSITE AT [WWW.DOW.COM](http://WWW.DOW.COM), OR FROM YOUR DOW SALES APPLICATION ENGINEER, OR DISTRIBUTOR, OR BY CALLING DOW CUSTOMER SERVICE.

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

®™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

© 2021 The Dow Chemical Company. All rights reserved.

2000008264

Form No. 95-1131-01-0121 S2D